



## **SB 2130 Limestone Neutralizer**

SB 2130 Limestone Neutralizer is the second step of the two-step method of cleaning light to moderate limestone surfaces. It may also be used as a one step cleaner for some lightly soiled surfaces. SB 2130 is always used after cleaning limestone, unpolished marble or concrete with either SB 2120 Limestone Prep, SB 2140 Masonry Restorer NA or SB 2150 Heavy-Duty Carbon Crust Remover. SB 2130 consists of a mild organic acid that serves as a neutralizer, cleaner and brightener of calcareous surfaces.

### **Preparation**

Provide protection for foliage and pedestrian traffic. Shut off all ventilation intakes, close all other entrances to the structure, provide temporary caulking if required and provide protection so that no cleaner or cleaner fumes enter the structure during application and rinsing of the surface. Protect all surrounding areas from possible damage which might occur from spillage or spray during usage.

All projects should start with a series of test applications to determine the suitability of the cleaner for the subject surface and to determine the proper dilution ratio. Some projects might require different dilutions for different masonry that may be a part of the same facade. Test areas of approximately 10 square feet are recommended for each type of masonry surface and should be left to age for 10 or more days to determine if there are any latent reactions that might require a modification of the cleaning method or products.

### **Dilution and Coverage**

Dilution varies dependent on the surface, porosity of the surface and degree of soiling/stains, etc. Initial recommended dilution is 0 to 3 parts water to 1 part product. Test application is highly recommended to determine dilution rate and appropriate dwell time. Optimum dwell time and dilution rate may change with weather conditions.

Coverage: Dependent upon substrate and other conditions

### **Application**

If the SB 2130 Limestone Neutralizer is being used as a one step cleaner, the surface should be pre-wet prior to application. When using SB 2130 as a neutralizer, the properly diluted solution must be applied to the surface immediately after removal of the Step 1 cleaner and prior to the drying of the surface. The preferred application method is by low-pressure spray. The use of brushes and rollers might contaminate the neutralizer during reloading of the applicator. SB 2130 should be used undiluted or diluted with 1 part water when used as a one-step cleaner or as the neutralizer for SB 2150. Dilutions with 2 to 3 parts water can be acceptable when used as a neutralizer for SB 2120 Limestone Prep or SB 2140 Masonry Restorer NA.

SB 2130 Limestone Neutralizer is for use by professional contractors only. When using SB 2130, as part of a two-step cleaning system, always refer to the Step 1 data sheet [SB 2120, SB 2140 or SB 2150] in conjunction with the SB 2130 data sheet to assure the proper usage for the system.

### **Technical Data**

Appearance: Clear Liquid	pH: 4
Biodegradable: Yes	Rinsing: Complete
Flash Point: None	Solubility: 100%
Foaming: None	Stability: Good
Odor: Vinegar	Wetting Ability: Excellent

### **Safety**

Causes severe skin burns and eye damage. Causes serious eye damage.



**DANGER**

Refer to product SDS or product label for hazard statements, precautionary statements and safety information

### **Warranty**

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

### **Contact**

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.