



SB 2220 Safe Strip

SB 2220 Safe Strip is a thick, clinging paint remover based on biodegradable ingredients. It can remove a variety of water and solvent borne paints, sealers, enamels and other coatings from masonry, wood and metal surfaces. SB 2220 can be used in the removal of graffiti done with marking pens, some spray paints and lacquers. SB 2220 is non-flammable, non-acid, non-caustic, and does not have a strong odor. It is ideal for both indoor and outdoor use. SB 2220 will not bleach wood like many caustic paint strippers.

Preparation

Provide protection for pedestrians, vehicles, roofing and foliage. Test all other non-masonry surfaces for negative reactions and provide protection where required. Remove all loose materials from the surface prior to application. Protect all surrounding areas from possible damage due to spillage or drippage during application.

All projects should start with a test application to determine suitability of the material for the chosen project, method of application and dwell time. Not all paints can be removed by this product.

Dilution and Coverage

Dilution: Do not dilute this product

Coverage: Dependent upon substrate and other conditions

Application

Apply SB 2220 with solvent resistant brushes or rollers. Allow the remover to work for at least 15 minutes. If there is a heavy buildup of coating to be removed, agitation with a brush to work the stripper into the coating is often beneficial. Depending on the type of coating, the number of coats, and the ambient temperature, a dwell time of up to several hours may be necessary. Do not let surface dry. Remove bulk of loosened paint with mechanical scraper if conditions permit. Use high pressure water to remove remaining paint and stripper from masonry. Repeat as necessary for complete removal of coating. If the stripper dries before it can be removed, reapplication may be required to soften the dried material. Neutralization of the surface, after removal and rinsing, is not required.

SB 2220 Safe Strip is for use by professional contractors only.

Technical Data

| | |
|--------------------|----------------------------|
| Appearance: Milky | pH: 8 |
| Biodegradable: Yes | Rinsing: Complete |
| Flash Point: None | Solubility: Emulsifiable |
| Foaming: No | Stability: Good |
| Odor: Low | Wetting Ability: Excellent |

Safety

Causes serious eye damage.



DANGER

Refer to product SDS or product label for hazard statements, precautionary statements and safety information

Warranty

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

Contact

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.