

# **SB 2240 Coating Stripper**

SB 2240 Coating Stripper is a powerful blend of solvents designed to remove cured coatings and films from exterior concrete and masonry surfaces. This product does not contain methylene chloride or any other chlorinated solvents.

\*\* For Professional Use Only \*\*

#### **Preparation**

Provide protection for pedestrians, vehicles, roofing and foliage. Test all other non-masonry surfaces for negative reactions and provide protection where required. Remove all loose materials from the surface prior to application. Protect all surrounding areas from possible damage due to spillage or drippage during application. All projects should start with a test application to determine suitability of the material for the chosen project, method of application and dwell time.

## **Dilution and Coverage**

Dilution: Product is used undiluted

Coverage: Dependent upon substrate and other conditions

#### **Application**

This product is not for general coatings removal use. It should not be used in inhabited structures.

Application of this product should be done with natural fiber brush or cloth. This material will attack many types of plastic including some synthetic fibers used in paint brushes. Let dwell 10 - 15 minutes and rinse with pressure washer or scrape loosened paint and rinse with water.

Flammable Liquid (Contains Dimethyl Carbonate) The flash point of this material is 60°F. This means that dangerous accumulations of flammable or explosive vapors can be created under normal usage conditions. Do not store nor use near fire of flame. Keep away from potential ignition sources. Solvent soaked rags present a fire hazard. Do not use in confined spaces. Provide mechanical ventilation and/or respirator with organic vapor cartridge.

Skin penetration potential (Contains N-methyl 2-pyrrolidone) This solvent can penetrate the skin faster than most others commonly used. This means that the solvent and whatever is dissolved in it can enter the bloodstream via skin contact. User must wear solvent proof rubber gloves at all times. Do not use to remove chemicals from skin or clothing.

### **Technical Data**

Appearance: Clear Liquid pH: NA

Biodegradable: Yes Rinsing: Complete
Flash Point: 57 Degrees F Solubility: 100%
Foaming: NA Stability: Good

Odor: Strong Solvent Wetting Ability: Excellent

## Safety

Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May damage fertility or the unborn child.







**DANGER** 

Refer to product SDS or product label for hazard statements, precautionary statements and safety information. Organic vapor protection respirators and solvent-resistant skin protection must be worn.

#### Warranty

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

## Contact

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.