



## **SB 2650 EIFS Protective Clear Coat**

SB 2650 EIFS Protective Clear Coat is designed for application over existing sound EIFS surfaces to provide protection from graffiti, most organic growth and the effects of acid rain deterioration. SB 2650 is a clear water based micro dispersion of an elastomeric silicone resin. SB 2650 is very UV resistant but is transparent to UV rays which allows for an even change in color when only a portion of the structure is treated. This product is designed for use with SB 2660 EIFS Graffiti Remover for the removal of most common types of graffiti. When properly applied, SB 2650 EIFS can greatly extend the service life of an EIFS surface that is in the early stages of breakdown as well as provide for the easy removal of most offensive graffiti. SB2650 might also be considered for treatment of new EIFS surfaces when the construction site is in a known graffiti prone area.

### **Preparation**

Apply SB 2650 to properly cleaned and dry surfaces only. Protect all non EIFS surfaces from dripping or over spray. Provide protection for windows, foliage, adjacent surfaces that are not to receive treatment, vehicle and pedestrian traffic. Take precautions to protect other surfaces from wind drift.

Using the method to be used on the project, apply a test area of 10 square feet to calculate the coverage rate per gallon and to determine if there will be any unacceptable color change.

### **Dilution and Coverage**

Dilution: This product is used undiluted -- test application recommended. This product is a single application only. Coverage: 150 to 200 square feet per gallon -- dependent upon substrate and other conditions

This product can be diluted with 1 to 2 parts water to 1 part product and used as a masonry water repellent for vertical surfaces.

### **Application**

A flood coat spray application is highly recommended but roller applications can be successful as long as there is a sufficient amount of solids deposited on the surface to meet performance standards. Apply with a coarse low pressure spray creating a saturating 4 to 6 inch run down of the fluid. For some coarse finishes, a spray and back roll with a one half inch nap roller that is saturated with SB 2650 may be the best means of application to avoid streaks. Clean application equipment with soap and water immediately after usage.

All EIFS surfaces must be free of any agent or agents that will prevent adhesion of the coating. Application should not be undertaken when rain is eminent within 12 hours or if there is frost or ice on the surface. The best results are obtained when surface and ambient temperatures are 40 degrees and rising and below 95 degrees. Do not alter the product with any other material. SB 2650 is not acceptable for application over other

anti graffiti treatments or non-standard EIFS coatings. If the coating comes in contact with window glass or other non-EIFS surfaces, remove immediately with a water soaked rag or pressure washer. SB 2650 applications may cause a slight color enhancement of some surfaces. Testing is recommended, prior to the start of a project, to determine if there are any appearance changes that are unacceptable. Graffiti removal agents, other than SB 2660 EIFS Graffiti Remover, may cause damage to the SB 2650 treatment and or the underlying EIFS system. Repainting with EIFS paints may not be possible without first removing the SB 2650.

### **Technical Data**

Appearance: Milky Liquid	pH: 7
Odor: Mild	Stability: Good

### **Safety**

There are no GHS ratings that apply to this product at this time.

Refer to product SDS or product label for hazard statements, precautionary statements and safety information

### **Warranty**

Shore Corporation warrants that this product conforms to the chemical composition described in the Product Label. SHORE CORPORATION EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Shore Corporation shall not be responsible for any direct or consequential damages sustained as a result of the use of this product. Further, Shore Corporation shall not be liable for personal injuries, property damage or any other damages as a result of the use of this product, the sole responsibility of Shore Corporation under the within WARRANTY being the replacement of any nonconforming product. Acceptance and use of this product absolves Shore Corporation from any other such liability whatsoever and from whatever source. The within WARRANTY may not be modified or extended by Shore Corporation representatives or distributors, neither of which are empowered to make any product representation inconsistent with the terms hereof.

### **Contact**

Trained representatives are available to assist with project assistance and product recommendations. Call **412/471-3330**.