

Safety Data Sheet (SDS)

Section 1 - Chemical Product and Company Information

Product Name: SB 2412 Matte Masonry Enhancer OTC VOC 400 Product Code: A854

Manufacturer:
Shore Corporation
2917 Spruce Way
Pittsburgh, PA 15201

Telephone 412-471-3330
Toll free 800-860-4978
Fax 412-471-3260
www.shorecorporation.com

In case of transportation or
chemical emergency contact:

ChemTel, Inc
1-800-255-3924 (24 hours)

Product Use: Concrete and masonry sealer
Not recommended for: Food contact surfaces

Section 2 - Hazards

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: >= 1.5 < 2.3
Carcinogen	2	Limited evidence of human or animal carcinogenicity
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm ² /s at 40° C.

GHS Hazards

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H316	Causes mild skin irritation
H351	Suspected of causing cancer

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/.../equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge

P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P331	Do NOT induce vomiting
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P370+P378	In case of fire: Use dry chemical, carbon dioxide, foam, or sand for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with local/ regional/ national/, regulations.

Signal Word: Danger



Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product. .

Section 3 - Composition

Chemical Name	CAS number	Weight Concentration %
tert butyl acetate	540-88-5	60.00% - 70.00%
Solvent Naphtha (Petroleum), Light Aromatic	64742-95-6	5.00% - 10.00%
Aromatic 150 Fluid	64742-94-5	1.00% - 5.00%
1,2,4-Trimethylbenzene	95-63-6	1.00% - 5.00%
Naphthalene	91-20-3	0.10% - 1.00%

Section 4 - First Aid Measures

INHALATION - Take affected persons out into the fresh air. Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

INGESTION - If material is ingested, seek immediate medical attention. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.

Notes to Physician: If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

If necessary oxygen respiration treatment.

Section 5 - Fire Fighting Measures

Flash Point: 4 C (39 F)

LEL: 1.00

UEL: 7.00

EXTINGUISHING MEDIA: Use carbon dioxide (CO2), "alcohol" foam, dry chemical, or sand.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback. Product can float on water stream to spread fire.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Do not store together with acids.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

REGULATORY REQUIREMENTS: No data found.

Section 8 - Exposure Controls / Personal Protection			
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
tert butyl acetate 540-88-5	TWA 200ppm 950 mg/m3	TWA 200 ppm	NIOSH IDLH 1500 ppm
Solvent Naphtha (Petroleum), Light Aromatic 64742-95-6	PEL 50 ppm	TLV 50 ppm	Not Established
Aromatic 150 Fluid 64742-94-5	Not Established	Not Established	Not Established
1,2,4-Trimethylbenzene 95-63-6	Not Established	Not Established	NIOSH - Recommended Exposure Limits Value = TWA Control Parameters = 25 ppm 125 mg/m3
Naphthalene 91-20-3	Value = TWA Control Parameters = 10 ppm 50 mg/m3	Value = TWA Control Parameters = 10 ppm Value = STEL Control Parameters = 15 ppm Biological Exposure Indices - BEI	NIOSH - Limits Value = TWA Control Parameters = 10 ppm 50 mg/m3 Value = STEL Control Parameters = 15 ppm 75 mg/m3

ENGINEERING: Do not use near fire or flame.

VENTILATION: Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits. Use mechanical ventilation to reduce buildup of vapors in enclosed areas.

ADMINISTRATIVE CONTROLS: Read SDS and follow recommended procedures.

PROTECTIVE EQUIPMENT: Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

Respiratory protection may not be needed if the local exhaust is sufficient to maintain levels of hazardous ingredients below occupational exposure limits. If needed, use a NIOSH/MSHA approved respirator equipped with a full facepiece, organic vapor cartridges, and high-efficiency, particulate air (HEPA) filters. Do not use respirators beyond their capabilities. FOR EMERGENCIES AND UNKNOWN CONCENTRATIONS, use supplied-air respiratory protection or a positive-pressure, self-contained breathing apparatus (SCBA).

CONTAMINATED EQUIPMENT: Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance: Clear liquid Vapor Pressure: 38.7 mmHg Vapor Density: 4.3 Specific Gravity: 0.93 Freezing point: No Data Boiling range: 98°C Evaporation rate: No Data Partition coefficient (n-octanol/water): No Data Decomposition temperature: No Data Grams VOC less water: No Data	Odor: Strong solvent Odor threshold: No Data pH: Not Applicable Melting point: No Data Solubility: No Data Flash point: 4C Flammability: No Data Autoignition temperature: No Data Viscosity: No Data
---	--

Section 10 - Stability and Reactivity

Stability: Hazardous polymerization will not occur.

STABLE

Components of this mixture are incompatible with the following materials: Oxidizers. This mixture may soften certain plastics and rubbers.

This mixture is likely to exhibit the following combustion products:
Oxides of carbon and nitrogen

Section 11 - Toxicological Information

Mixture Toxicity

Dermal Toxicity LD50: 2,914mg/kg

Inhalation Toxicity LC50: 112mg/L

Component Toxicity

540-88-5	tert butyl acetate Oral LD50: 4,100 mg/kg (rat) Dermal LD50: 2,001 mg/kg (rabbit)
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic Dermal LD50: 3,160 mg/kg (rabbit) Inhalation LC50: 2,900 ppm (rat)
64742-94-5	Aromatic 150 Fluid Dermal LD50: 2,001 mg/kg (Rabbit)
91-20-3	Naphthalene Oral LD50: 490 mg/kg (Rat) Inhalation LC50: 340 mg/L (Rat)

Exposure to this material may affect the following organs:

Central Nervous System Respiratory System

Effects of Overexposure

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic	5 to 10%	Cumene CAS 98-82-8 IARC 2B NTP SUS
91-20-3	Naphthalene	0.1 to	IARC: Group 2B: Possibly carcinogenic to humans NTP: Reasonably anticipated to be a human carcinogen OSHA: Not a carcinogen

Section 12 - Ecological Information

Ecological information: No data found.

Component Ecotoxicity

tert butyl acetate	EC50: 16 mg/l Exposure time: 72 HOURS Species: Pseudokirchneriella subcapitata (green algae) Growth inhibition : EC50: 64 mg/l Exposure time: 96 HOURS No data for
Solvent Naphtha (Petroleum), Light Aromatic	LC50 (Fish, 96hr) 41 & 45mg/litre (Pimephelas promelas), 2.34, 9.22mg/litre (Oncorhynchus mykiss), 119mg/litre (Alburnus alburnus), 82mg/litre (Cyprinodon variegatus), EC50 (Crustacea, 24hr) 6.1, 170 & 226mg/litre (Daphnia magna) EC50 (Algae) 19 & 56mg/litre (Selenastrum capricornutum), 3.3mg/litre (Skeletonema costatum)

Aromatic 150 Fluid	Test	Duration	Organism Type
	Test Results		
	Aquatic - Acute Toxicity	72 hour(s)	Pseudokirchneriella subcapitata EL50 11 mg/l: data for the material
	Aquatic - Acute Toxicity	72 hour(s)	Pseudokirchneriella subcapitata NOELR 2.5 mg/l: data for the material
	Aquatic - Acute Toxicity	96 hour(s)	Oncorhynchus mykiss LL50 >=2 - <=5 mg/l: data for the material
	Aquatic - Acute Toxicity	48 hour(s)	Daphnia magna EL50 >=3-<=10 mg/l: data for the material
1,2,4-Trimethylbenzene	Toxicity to fish Flow-through test LC50 - Pimephales promelas (fathead minnow) - 7.72 mg/l - 96 hrs.		
	Toxicity to daphnia and other aquatic invertebrates Static test EC50 - Daphnia magna (Water flea) - 3.6 mg/l - 48 hrs. (OECD Test Guidelines 202)		
Naphthalene	Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 0.9 - 9.8 mg/l - 96.0 h LC50 - Pimephales promelas (fathead minnow) - 1 - 6.5 mg/l - 96.0 h NOEC - other fish - 1.8 mg/l - 3.0 d LOEC - other fish - 3.2 mg/l - 3.0 d		
	Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 1.00 - 3.40 mg/l - 48 h		
	Toxicity to algae EC50 - No information available. - 33.00 mg/l - 24 h		

Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transport Information

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
US DOT	Flammable liquids, n.o.s. (butyl acetates)	UN1993	II	3

Section 15 - Regulatory Information

Additional regulatory listings, where applicable.

The following chemicals are listed in MA RTK
91-20-3 Naphthalene 0.1 to 1.0 %
95-63-6 1,2,4-Trimethylbenzene 1 to 5 %
540-88-5 tert butyl acetate 60 to 70 %

The following chemicals are on the NJ RTK list:

91-20-3 Naphthalene 0.1 to 1.0 %
95-63-6 1,2,4-Trimethylbenzene 1 to 5 %
64742-94-5 Aromatic 150 Fluid 1 to 5 %
540-88-5 tert butyl acetate 60 to 70 %

The following chemicals are on the NY RTK list

91-20-3 Naphthalene 0.1 to 1.0 %

The following chemicals are on the PA RTK list

91-20-3 Naphthalene 0.1 to 1.0 %
95-63-6 1,2,4-Trimethylbenzene 1 to 5 %
64742-94-5 Aromatic 150 Fluid 1 to 5 %
540-88-5 tert butyl acetate 60 to 70 %

The following chemicals are listed under Prop 65

91-20-3 Naphthalene 0.1 to 1.0 %
95-63-6 1,2,4-Trimethylbenzene 1 to 5 %
64742-94-5 Aromatic 150 Fluid 1 to 5 %

Country

Canada
US

Regulation

Canadian Domestic Substances List
Toxic Substances Control Act

All Components Listed

No
Yes

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Section 16 - Other Information


Hazardous Material Information System (HMIS)

HEALTH	1
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH
4 = SEVERE

National Fire Protection Association (NFPA)



DISCLAIMER AND NON-WARRANTY: This Safety Data Sheet was prepared by Shore Corporation and is correct to the best of our knowledge, information and belief at the date of its publication. The information came from raw material suppliers, regulatory databases, and/or third parties

with expertise in this area. This information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. No warranties of any kind, either expressed or implied, including warranties of the accuracy of the information presented and the suitability of a product for a particular purpose.

Reviewer Revision

Date Prepared: 8/28/2015