

Safety Data Sheet (SDS)

Section 1 - Chemical Product and Company Information

Product Name: SB2423 Seretreat 10% 400 OTC Product Code: A831

Manufacturer: Shore Corporation
2917 Spruce Way
Pittsburgh, PA 15201

Telephone 412-471-3330
Toll free 800-860-4978
Fax 412-471-3260
www.shorecorporation.com

In case of transportation or chemical emergency
contact:

ChemTel, Inc
1-800-255-3924 (24 hours)

Product Use: Wood and Masonry water repellent
Not recommended for:

Section 2 - Hazards

GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Reproductive toxin	2	Human or animal evidence possibly with other information

GHS Hazards

H226	Flammable liquid and vapour
H361	Suspected of damaging fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/.../equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P308+P313	IF exposed or concerned: Get medical advice/attention
P370+P378	In case of fire: Use ... for extinction

P405
P403+P235
P501

Store locked up
Store in a well ventilated place. Keep cool
Dispose of contents/container in accordance with local/ regional/ national/
regulations.

Signal Word: Warning



Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product. Impaired kidney and liver functions from preexisting disorders may be aggravated by exposure to this product.

Kidney damage may be evidenced by changes in urine output, urine appearance, or edema (swelling from fluid retention). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

Section 3 - Composition

Chemical Name	CAS number	Weight Concentration %
Octamethylcyclotetrasiloxane	556-67-2	80.00% - 90.00%
Naphtha (petroleum), heavy alkylate	64741-65-7	5.00% - 10.00%

Section 4 - First Aid Measures

INHALATION - Take affected persons out into the fresh air. Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing.
In case of irregular breathing or respiratory arrest provide artificial respiration.
In case of unconsciousness place patient stably in side position for transportation.

EYE CONTACT - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

SKIN CONTACT - Immediately remove any clothing soiled by the product.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

INGESTION - If material is ingested, seek immediate medical attention. If vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs.

Notes to Physician: If swallowed, gastric irrigation with added, activated carbon.
If swallowed or in case of vomiting, danger of entering the lungs.
If necessary oxygen respiration treatment.

Section 5 - Fire Fighting Measures

Flash Point: 51 C (124 F)

LEL: 1.00

UEL: 7.00

EXTINGUISHING MEDIA: Use carbon dioxide (CO₂), "alcohol" foam, dry chemical, or sand. Do not use water spray.

UNUSUAL FIRE OR EXPLOSION HAZARDS: The product vapor is heavier than air and may travel a considerable

distance to a source of ignition and flashback. Product is water reactive and may produce hydrogen gas in contact with water.

HAZARDOUS COMBUSTION PRODUCTS: See section 10 for a list of hazardous decomposition products for this mixture.

FIRE FIGHTING: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

FIRE FIGHTING EQUIPMENT: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

SPILL AND LEAK PROCEDURES: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

SMALL SPILLS: Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

LARGE SPILLS: Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Using nonsparking tools, mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 7 - Handling and Storage

HANDLING PRECAUTIONS: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

STORAGE: Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

Do not store together with acids.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

REGULATORY REQUIREMENTS: No data found.

Section 8 - Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Octamethylcyclotetrasiloxane 556-67-2	Not Established	Not Established	Not Established
Naphtha (petroleum), heavy alkylate 64741-65-7	Z-1 CAS 8052-41-3 TWA 500 ppm 2,900 mg/m3	TWA 100 pp,	Not Established

ENGINEERING: Do not use near fire or flame.

VENTILATION: Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits. Use mechanical ventilation to reduce buildup of vapors in enclosed areas.

ADMINISTRATIVE CONTROLS: Read SDS and follow recommended procedures.

PROTECTIVE EQUIPMENT: Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

Respiratory protection may not be needed if the local exhaust is sufficient to maintain levels of hazardous ingredients below occupational exposure limits. If needed, use a NIOSH/MSHA approved respirator equipped with a full facepiece, organic vapor cartridges, and high-efficiency, particulate air (HEPA) filters. Do not use respirators beyond their capabilities. FOR EMERGENCIES AND UNKNOWN CONCENTRATIONS, use supplied-air respiratory protection or a positive-pressure, self-contained breathing apparatus (SCBA).

CONTAMINATED EQUIPMENT: Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 9 - Physical and Chemical Properties

This mixture typically exhibits the following properties under normal circumstances:

Appearance: Clear liquid Vapor Pressure: 0.11 hPa Vapor Density: No Data Specific Gravity: 0.91	Odor: Mild amine Odor threshold: No Data pH: N/A Melting point: No Data
--	--

Freezing point: No Data Boiling range: 175°C Evaporation rate: No Data Explosive Limits: 1% - 7% Autoignition temperature: No Data Viscosity: No Data	Solubility: No Data Flash point: 124 F, 51 C Flammability: No Data Partition coefficient (n-octanol/water): No Data Decomposition temperature: No Data Grams VOC less water: No Data
--	---

Section 10 - Stability and Reactivity

Stability: Hazardous polymerization will occur if in contact with water! Hydrogen gas may be generated.

Components of this mixture are incompatible with the following materials: Oxidizers, strong alkalis, and acids. This mixture may soften certain plastics and rubbers.

This mixture is likely to exhibit the following combustion products:
Oxides of carbon, nitrogen, and silicon.

Section 11 - Toxicological Information

Mixture Toxicity

Dermal Toxicity LD50: 2,756mg/kg
Inhalation Toxicity LC50: 3,624mg/L

Component Toxicity

556-67-2 Octamethylcyclotetrasiloxane
Oral LD50: 4,800 mg/kg (Rat) Dermal LD50: 2,375 mg/kg (Rabbit) Inhalation LC50: 2,975 ppm (

Ingestion

Exposure to this material may affect the following organs:

Effects of Overexposure

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

Section 12 - Ecological Information

Ecological information: No data found.

Component Ecotoxicity

Octamethylcyclotetrasiloxane

Toxicity to fish: LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.022 mg/l, Exposure Time 96 h
Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia sp.): > 0.015 mg/l, Exposure Time 48 h
Toxicity to algae: EC50: > 0.022 mg/l, Exposure time 96 h
NOEC: 0022 mg/l, Exposure time 96 h

Naphtha (petroleum), heavy alkylate

Toxicity to fish (Acute toxicity): Remarks: Expected to be not toxic at limit of water solubility.
Toxicity to daphnia and other aquatic invertebrates (Acute toxicity): Remarks: Expected to be not toxic at limit of water solubility.
Toxicity to algae (Acute toxicity): Remarks: Expected to be not toxic at limit of water solubility.
Toxicity to fish (Chronic toxicity): Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity): Remarks: NOEC/NOEL expected to be > 1.0 - <= 10 mg/l
Toxicity to bacteria (Acute toxicity): Remarks: Expected to be practically non toxic: LC/EC/IC50 > 100 mg/l

Section 13 - Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transport Information

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
US DOT	Flammable Liquids, n.o.s. (Octamethylcyclotetrasiloxane)	UN1993	III	3

Section 15 - Regulatory Information

Additional regulatory listings, where applicable.

The following chemicals are on the NJ RTK list:

556-67-2 Octamethylcyclotetrasiloxane 80 to 90 %

The following chemicals are on the PA RTK list

556-67-2 Octamethylcyclotetrasiloxane 80 to 90 %

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
Canada	Canadian Domestic Substances List	No
US	Toxic Substances Control Act	Yes

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HEALTH	<input type="text"/>	1
FLAMMABILITY	<input type="text"/>	2
PHYSICAL HAZARD	<input type="text"/>	2
PERSONAL PROTECTION	<input type="text"/>	

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard

0 = INSIGNIFICANT


1 = SLIGHT

2 = MODERATE

3 = HIGH

4 = SEVERE

National Fire Protection Association (NFPA)



NON-WARRANTY. The information presented in this publication is based upon the research and experience of a fictitious entity (ABC Paint). No representation or warranty is made concerning the accuracy or completeness of the information presented in this publication. ABC Paint makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by ABC Paint are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. ABC Paint shall in no event be liable for any special, incidental, or consequential damages.

Reviewer Revision

Date Prepared: 6/1/2015